

KC5000



標準配件



920 公厘自動噴槍



10 公尺高壓軟管



插電式



25 秒後自動洩壓



機器停留 60 分鐘
後完全停止



熱控制閥系統

型號	KC5000	KC5050	KC6000
編碼	3.023.14.361	3.023.14.392	3.023.14.391
流量(L/H)	1260	1500	1800
壓力(BAR)	200	200	200
壓力 (PSI)	2901	2901	2901
轉速(RPM)	1750	1750	1750
馬力(HP)	10	15	15
馬力(KW)	7.5	11	11
電源線長度(M)	5	5	5
供電	220V/3Ø/60HZ	220V/3Ø/60HZ	220V/3Ø/60HZ
尺寸(長 x 寬 x 高)(CM)	120 x 75 x 105	120 x 75 x 105	120 x 75 x 105
重量(KG)	132	132	132



特點

- 帶駐車制動器的前樞軸輪
- Mazzoni專業幫浦
- 配電盤
- 塗漆鋼架
- Mazzoni自動洩壓
- Mazzoni安全閥
- 內部計時錶



馬達

- MAZZONI MEC系列免維護感應馬達，繞組採用熱敏保護。
- 彈性聯軸器



幫浦



- 專業幫浦(曲軸連桿)、銅頭、三個陶瓷活塞。

選配



軟管捲軸



除鏽噴砂組



噴嘴工具組



旋轉刷具



渦輪噴嘴



讀時器



清潔劑罐



外接清潔劑工具包



鋼柄 (訂購軟管捲軸)