

# W5000 熱水高壓清洗機



## 標準配件



920 公厘自動噴槍

15 度噴嘴

10 公尺高壓軟管

-全系列產品義大利製造-



25 秒後自動洩壓



機器停留 60 分鐘  
後完全停止



插電式



缺燃料時，加熱器不能  
工作啟動。



泄漏時啟動停止系統，  
總停止壓力達 15bar。



第六次重新啟動後，  
由於漏水而停止機器。



型號	W5000	W15-400
編碼	3.023.24.299	3.023.24.360
最高溫度(°C)	150	150
流量(L/H)	1260	900
壓力( BAR)	200	400
壓力(PSI)	2901	5801
轉速(RPM)	1750	1750
馬力(HP)	10	15
馬力(KW)	7.5	11
電源線長度(M)	20	20
供電	220V/3Ø/60HZ	220V/3Ø/60HZ
尺寸(長 x 寬 x 高)(CM)	125 x 80 x 113	125 x 80 x 113
重量(KG)	200	200

# W5000 熱水高壓清洗機



## 特點

- 內置16公升清潔劑罐
- 每小時4公斤耗油量；30公升燃油箱
- 鍋爐防爆燃及保護斷電裝置
- 水溫及壓力調節器
- 停車控制閥
- 20公升雙漂浮供水箱
- 1.5公升副水箱自動防垢
- 超壓安全閥、洩壓安全閥保護
- 鍋爐、泵浦、機油、馬達、電壓及備用燃料警示燈
- 鍋爐防爆及保護斷電：防卡柴油泵浦、泵浦機油不足自動斷電
- 馬達用獨立風扇
- 鍋爐溫度控制系統－鍋爐過熱燈號顯示、燃油量不足熱水自動斷電
- 內部計時表（工作500小時後保養訊息提示）



## 馬達 MEC132M

- 歐盟高規格CE認證 (CE certificate)
- 業界獨家MAZZONI MEC系列免維護感應馬達，繞組採用熱敏保護
- 彈性聯軸器



## 泵浦

- 專業幫浦(附連接杆)、銅頭、三個陶瓷活塞

## 選配



安全清潔劑



旋轉刷具



除鏽噴砂組



軟管捲軸



煙囪頭



安全水位



渦輪噴嘴



噴嘴工具組



清潔劑閥



W5000 附槍把和軟管捲軸